

# TU854

## ABB Ability™ System 800xA® hardware selector



The TU854 MTU can have up to 8 I/O channels and 2+2 process voltage connections. Each channel has two I/O connections and one ZP connection. Input signals are connected via individual shunt sticks, TY801. The shunt stick is used to choose between voltage and current input. The maximum rated voltage is 50 V and maximum rated current is 2 A per channel. The MTU distributes the two ModuleBuses, one to each I/O module and to the next MTU. It also generates the correct address to the I/O modules by shifting the outgoing position signals to the next MTU.

The MTU can be mounted on a standard DIN rail. It has a mechanical latch that locks the MTU to the DIN rail.

Four mechanical keys, two for each I/O module, are used to configure the MTU for different types of I/O modules. This is only a mechanical configuration and it does not affect the functionality of the MTU or the I/O module. Each key has six positions, which gives a total number of 36 different configurations.

### Features and benefits

- Up to 8 channels of field signals and process power connections.
- Connections to two ModuleBuses and I/O modules.
- Mechanical keying prevents insertion of the wrong I/O module.
- Latching device to DIN rail for grounding.

| General info         |   |
|----------------------|---|
| Article number       | 3BSE069966R1  |
| Type                 | Redundant   |
| Connection           | 25 pin D-sub  |
| Channels             | 16  |
| Voltage              | 50 V  |
| Mounting             | Horizontal  |
| Mounting detail      | 55 °C (131 °F)  |
| Use with I/O         | AI845, AI880A and DP840   |
| Process connections  | up to 8 I/O channels (2 terminals per channel)<br>D-sub connector 25 pin (male) |
| Single/redundant I/O | Redundant   |

| Detailed data                      |            |
|------------------------------------|------------|
| Maximum current per I/O channel    | 2 A        |
| Maximum current process connection | 5 A        |
| Dielectric test voltage            | 500 V a.c. |

| Environment and certification   |   |
|---------------------------------|---|
| CE mark                         | Yes   |
| Electrical safety               | EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201              |
| Hazardous Location              | ATEX Zone 2 to be released 2016                                     |
| Marine certification            | -   |
| Temperature, Operating          | 0 to +55 °C (+32 to +131 °F), approvals are issued for +5 to +55 °C |
| Temperature, Storage            | -40 to +70 °C (-40 to +158 °F)                                      |
| Pollution degree                | Degree 2, IEC 60664-1   |
| Corrosion protection            | ISA-S71.04: G3  |
| Relative humidity               | 5 to 95 %, non-condensing   |
| Max ambient temperature         | 55 °C (131 °F)  |
| Protection class                | IP20 according to IEC 60529   |
| Mechanical operating conditions | IEC/EN 61131-2  |
| EMC                             | EN 61000-6-4, EN 61000-6-2  |
| Overvoltage categories          | IEC/EN 60664-1, EN 50178  |
| Equipment class                 | Class I according to IEC 61140; (earth protected)                   |
| RoHS compliance                 | EN 50581:2012   |
| WEEE compliance                 | DIRECTIVE/2012/19/EU  |

| Dimensions |   |
|------------|---|
| Width      | 131 mm (5.16 in.) including connector, 124 mm (4.88 in.) edge to edge installed |
| Depth      | 64 mm (2.52 in.) including terminals  |
| Height     | 186.5 mm (7.34 in.) including locking device                                    |
| Weight     | 260 g (9.17 oz)   |

---

**[solutions.abb/800xA](https://solutions.abb/800xA)**  
**[solutions.abb/controlsystems](https://solutions.abb/controlsystems)**

---

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved